




Key Features

- LED A19 E26, GU24 base bulb
- Mercury and UV free
- Lasts up to 25,000 hours
- Instant start
- Power factor greater than 0.9
- Triac dimming
- UL Listed, Energystar qualified

Dimensions



Watt	Height	Width
5.5W, 6W	4.19"	2.35"
8W, 9W	4.23"	2.37"
15W	4.56"	2.36"
GU24	4.3"-4.67"	2.36"

Specification

Order Number	Socket Base	Watt	Lumens	Dimming	Voltage	CRI	CCT
L/A19/5.5/D1/830/L011	E26	5.5W	480	Triac	120V	80	3000K
L/A19/6/D1/830/L003	E26	6W	480	Triac	120V	80	3000K
L/A19/6/D1/840/L003	E26	6W	480	Triac	120V	80	4000K
L/A19/8/D1/830/L011	E26	8W	800	Triac	120V	80	3000K
L/A19/9/D1/830/L003	E26	9W	800	Triac	120V	80	3000K
L/A19/9/D1/840/L003	E26	9W	800	Triac	120V	80	4000K
L/A19/15/D1/830/L002	E26	15W	1600	Triac	120V	80	3000K
L/A19/15/D1/840/L002	E26	15W	1600	Triac	120V	80	4000K
L/A19GU24/6/D1/830/L003	GU24	6W	480	Triac	120V	80	3000K
L/A19GU24/6/D1/840/L003	GU24	6W	480	Triac	120V	80	4000K
L/A19GU24/9/D1/830/L003	GU24	9W	800	Triac	120V	80	3000K
L/A19GU24/9/D1/840/L003	GU24	9W	800	Triac	120V	80	4000K
L/A19GU24/15/D1/830/L003	GU24	15W	1600	Triac	120V	80	3000K
L/A19GU24/15/D1/840/L003	GU24	15W	1600	Triac	120V	80	4000K

