



Key Features

- LED Traditional Wall Pack
- Omni-directional wide light distribution
- Durable glass lens
- Surface mount
- High efficiency light
- Suitable for wet location


Reference	Wattage	Lumen
L/WPTR/30/XU/750/A001 [blank PC]	30W	3101
L/WPTR/40/XU/750/A001 [blank PC]	40W	4833
L/WPTR/60/DU/750/A001 [blank PC]	60W	7447
L/WPTR/100/XU/750/A001 [blank PC]	100W	10122

The LED Wall Pack series light distills the benefits of the latest in LED technology into a high performance, high efficacy, long-life fixture. The outstanding photometric performance results in delivering even light output with proven energy savings and a long average lifetime.

The LED x are a better alternative to incandescent, HID, Halogen and fluorescent with quick payback and improved performance. Boasts typical energy savings and long life of the product requires less lamp and ballast maintenance.

Applications: Commercial and industrial building wall

Dimensions



Electrical Data

- Input Voltage: 120/277VAC, 50/60Hz
- Power factor: >0.9

Qualifications

- Highly directional intense light optics technology
- Durable glass lens
- IP65 rated for outdoor use
- 5-year manufacturer warranty
- UL-listed, DLC-qualified

Ordering Information

Category	Wattage	Voltage	CCT	Vers.
L/WPTR	30	DU 120-277V	740 4000K	A001
	40		750 5000K	
	60			
	100			